

Assembly of SYNERGY'S EAB Trap

Traps, available in purple or green (shown) are sold in pairs and are shipped with glued faces touching. Whenever possible they should be assembled in the field. If only one trap will be used, cover the sticky surface of the other trap with wax paper. Glue is not water soluble, but can be removed with nail polish remover, acetone, or paint thinner.

ASSEMBLY

1. Separate two traps by pulling apart along long axis .
2. Carefully fold trap into 3 sections using the deep creases on trap. Glued surface should be on the outside.
3. Fold 2 inch edge with slots to inside, and insert tabs into slots. Secure with twist ties at top and bottom of trap.
4. Hook each arm of the hanger (optional) into center holes of the 3 trap sections.
5. Attach lure with twist-tie (included) to the small opening at the top of the hanger.

DEPLOYMENT

1. Attach a weight (tennis balls are good) to one end of fishing line and the other end to nylon rope (3/16th" recommended), and throw weight over tree branch.
2. Pull fishing line until nylon rope is within reach. Attach rope to trap using large top hole in hanger, and pull up into tree to desired height.
3. To facilitate 'steering' while pulling into tree, attach another rope into the one of the holes in the bottom of the trap to guide the trap up. Tie both ropes to tree (do not tangle ropes). In this fashion, the bottom rope will also act as a stabilizer against the wind.

PLACEMENT

Choose trees carefully, preferably with a diameter at breast height of 8". Use a branch stable enough to support weight of trap, and in as sunny a location as possible.



FOLD EDGE TO INSIDE TO
INSERT TABS



TWIST TIES

LURE PLACEMENT



HANGER



HOIST ROPE OVER BRANCH



Synergy Semiochemical Corporation

Phone: 604 454-1122 Fax: 604 568-8502

Email: synergy@semiochemical.com

Web: www.semiochemical.com